
RRPproxypy Documentation

Smoose BV

Feb 18, 2019

Contents:

1	rrpproxy reference	1
1.1	Client	1
1.2	Helpers	2
2	Indices and tables	3
	Python Module Index	5

1.1 Client

class `rrpproxy.client.RRPProxy` (*username, password, test=False*)

Bases: `object`

domain_price (*domain, **params*)

Get the price for an action on a domain.

Parameters

- **domain** (*str*) – The domain name.
- ****params** – Additional params.

Returns The response.

Return type `dict`

Raises `Failure` – When the request has failed.

Note: See the wiki for more info: <https://wiki.rrpproxy.net/api/api-command/DomainPrice>

get_zone_info (*zone, **params*)

Get information about a zone (TLD).

Parameters

- **zone** (*str*) – The zone to query.
- ****params** – Additional params.

Returns The response.

Return type `dict`

Note: See the wiki for more info: <https://wiki.rrpproxy.net/api/api-command/GetZoneInfo>

query_domain_list ()

Query a list of domains.

Returns A list of domains.

request (*command*, ***args*)

Perform a request.

Parameters **command** (*str*) – The API command to call.

Keyword Arguments **arguments to the API call.** (*Additional*) –

Returns The parsed response.

status_domain (*domain*)

Request the domain status.

Parameters **domain** (*str*) – The domain name to request the status for.

Returns The domain.

Return type dict

`rrpproxypy.client.try_parse` (*value*)

Try to parse the given value.

Parameters **value** (*str*) – The value to parse.

Returns The parsed value.

1.2 Helpers

`rrpproxypy.args.add_arguments` (*parser*, *default_username=None*, *default_password=None*)

Add RRP arguments to an argument parser.

Command line arguments are added for the RRP username (`--rrpproxy-username`) and password (`--rrpproxy-password`). Both default to environment variables (`RRPPROXY_USERNAME` and `RRPPROXY_PASSWORD`). Another default can be supplied which serves as a fallback for the environment variables.

Parameters **parser** (*ArgumentParser*) – The parser to add the arguments to.

Keyword Arguments

- **default_username** (*str*) – The default RRP username.
- **default_password** (*str*) – The default RRP password.

CHAPTER 2

Indices and tables

- `genindex`
- `modindex`
- `search`

r

`rrpproxy.py.args`, [2](#)
`rrpproxy.py.client`, [1](#)

A

`add_arguments()` (in module `rrpproxy.py.args`), 2

D

`domain_price()` (`rrpproxy.py.client.RRPproxy` method), 1

G

`get_zone_info()` (`rrpproxy.py.client.RRPproxy` method), 1

Q

`query_domain_list()` (`rrpproxy.py.client.RRPproxy` method), 2

R

`request()` (`rrpproxy.py.client.RRPproxy` method), 2

`RRPproxy` (class in `rrpproxy.py.client`), 1

`rrpproxy.py.args` (module), 2

`rrpproxy.py.client` (module), 1

S

`status_domain()` (`rrpproxy.py.client.RRPproxy` method), 2

T

`try_parse()` (in module `rrpproxy.py.client`), 2